## @ease Floating System for 300 Gallons

Filter:		

## Start-Up

- Once your hot tub is filled with water and filter(s) installed, bring a water sample to an Authorized Dealer and balance pH, alkalinity, and calcium hardness levels.
- Add Frog Jump Start Packet to hot tub for your start-up dose of shock.
- Connect the *Frog* @ease system and set the dial to #2.
- Place in the hot tub and forget about it for 3-4 weeks (or until the system flips)

## **Monthly**

- Change out @ease Chlorine Cartridge approximately every month (or when floater flips) and set to #2.
- Shock with <u>1 oz</u> of *Sirona Activate Granular*. Depending on usage and appearance water, you may need to shock weekly.
- Spray out filters, you can either use garden hose or a chemical filter cleaner such as, *Natural Chemistry Filter Perfect* or *Marquis Rapid Action Filter Cleaner*.
- Bring water sample to an Authorized Dealer to ensure all levels are in recommended ranges.

## **Every 3-4 Months**

- Drain & refill your hot tub. This amount of time is typical for draining however, an Authorized Dealer will keep track of you Total Dissolved Solids (TDS), once this number reaches ~1500, we will recommend draining & refilling your hot tub.
  - o It is also important to use *Pipe Cleanse* by *Natural Chemistry* every other time you drain & refill your hot tub. This will ensure that your lines are fully cleaned out of any bacteria or debris. Contact us for directions on how to use.
- Replace Frog @ease Mineral Cartridge every time you refresh the water.

\*Chlorine Cartridge = the <u>silver portion</u> of the floater, this must be replaced typically every 3-4 weeks, or whenever the floater flips.



<sup>\*</sup>Mineral Cartridge = the <u>blue portion</u> of the floater, this must be replaced every time the water is replaced.